

Traditional wallpaper

PR-001-27052021

Product despcription:	Decorative, surface printed wallpaper.
Suitability:	Suitable for most dry indoor wall surfaces, including hardboard and chipborad, plaster, plasterboard and timber. Not suitable for bathrooms or damp environments.
Adhesive:	Starch or cellulose-based adhesive.
Installation	
temperature:	+18-25C°
Roll lenght:	10,05 m or 11,2 m
Roll width:	48–54 cm
Paper weight:	120-130 g/m ²
Repeat and match:	Straight, half-drop or no match.
General attributes:	Wallpaper is printed on paper with traditional rotary-printing method. All printing colours are water-soluble, solvent free and or non-toxic distemper paints. They consist of cellulose starch, water, chalk, pigments and tinting pastes. The wallpaper is finished with a light fixative agent, that doesn't form a solid film or coating.
Batch number:	Batch number is marked on roll tag. Slight variations between different batches are possible; please ensure that all batch numbers are the same.
Washability:	Wallpaper is not washable. It can be cleaned only with a soft, dry cloth. Do not use any water or detergents.
Removability:	If the wallpaper should be removed, it can be done by applying water of diluted wallpaper paste on top of the paper. In few minutes the wallpaper can be peeled off.
Environment:	All wallpaper waste can be recycled to other materials or utilized as energy, according to your local recycling legistlation.



Hanging instructions

Mix wallpaper paste according to the manufacturer's instructions. We recommend using starch or cellulose based wallpapper powder, with no added glue or plastic. Walls should be prepared properly, creating a smooth and even surface. Measure height of the wall, and cut the length needed, plus 10—15 cm extra with a sharp knife. Apply paste evenly with a paste brush on the back of the wallpaper. Pay special attention to edges, apply thinly and evenly. Make sure that the paste does not end up on the patterned side of the wallpaper. Let wallpaper soak for 1—2 minutes, lift it gently (fold if needed) to the wall, align the pattern and attatch gently with a wallpaper brush. Handle wet wallpaper with care, as it is easily damaged. If the paste accidentally ends up on the pattern side of the wallpaper, dab it off quickly with a clean, dry cloth. See further hanging instructions and tips <u>www.tapettitehdas.fi/en/instructions/</u>

How to take care of your wallpapered wall? You can clean the wall lightly with a soft, dry fabric. Do not use water or detergents.

Please note:

Pihlgren and Ritola wallpapers are manufactured using traditional printing technique, high quality unbleached paper and water-based distemper paints. Every batch is unique and has its own, beautifully handmade appearance. Our wallpapers are products of traditional craftmanship, therefore minor variations in pattern are to be expected. Should you have any concerns about the quality of wallpaper, please contact your retailer.





CE	
21	
Pihlgren ja Ritola Oy, PL 43, FI-37801 Akaa, Finland	
+358 3542 1090	
PR-001-27052021	
EN 15102:2019	
Internal finishes of walls	
Rection to fire: D-s3,d2	
Release and emission of formaldehyde: compliant	
Migration of heavy metals and specific elements: compliant	
Release of vinyl chloride monomer: compliant	
Content of specific dangerous substances: compliant	
Emission of other dangerous substances into indoor air: compliant	
Sound absorption: NPD	
Thermal resistance: NPD	
https://www.tapettitehdas.fi/en/instructions	

This product specification is issued according to the best possible knowledge available to Pihlgren ja Ritola Oy. Information is based on laboratory tests, measurements, and first-hand experience. We cannot control the conditions in which the wallpaper is used, and therefore can only be held responsible of our own product, that fulfils all the quality standards available for traditional wallpaper. Our company does not bear any responsibility if the product is used against the Hanging Instructions or used against its original purpose. This product specification is up-to-date, and it replaces all previous specifications.